

Kerrick Shockproof Vacuum 90L

These vacuum cleaners have powerful 2 x 1000 watt (KVAC59PE/ KVAC59PE/P) or 3 x 1000 watt motors and a 90L litre tank capacity. Features include a high-impact corrosion-proof tank, large rear wheels and front castors for easier manoeuvring, large rear handle for enhanced mobility and a flexible hose with 50mm diameter accessories. The KVAC59PE/P comes with a submersible pump for transfer of greater volume of waste water. Manufactured in Italy, the KVAC59PE range and KVAC60PE shockproof vacuums offer quality, durability and performance. The Kerrick Shockproof Vacuums are high impact, corrosion-proof wet and dry vacuums designed for industrial use.

- Heavy duty shockproof vacuum
- High impact, corrosion proof tank
- Industrial 2 or 3 x 1000 watt motors (based on model) 90 litre container capacity
- Large rear wheels and front castors for easier manoeuvring
- Large rear handle for enhanced mobility
- Flexible 5m hose with 38mm diameter
- Full 38mm tool set



Picture shown may not represent model quoted

• Standard equipment

Included accessories		Ref. no.	Min. required	Kerrick 2 motor Wet and Dry Vacuum with high impac	Kerrick 2 motor Wet and Dry Vacuum with pump out	Kerrick 3 motor Wet and Dry Vacuum with high impac
Hose Vacuum Cleaner						
	Flexible Hose - 2.5 metre	VP6010648	0	•	•	•
Round Brush Nozzle						
	ROUND BRUSH	VP2511615	0	•		•
Crevice Nozzle						
	CREVICE TOOLI D.40	VP2511610	0	•		•
Filter						
	Textile Filter - SUITS KVAC59PE	VP6730000	0	•		•
Extension Tube						
	Chrome Extension 38mm	VP2511600	0	•	•	•
Squeegee, Blade, Skirt and Splash Guard						
	Squeegee Tool	VP6010011	0	•	•	•
Other						
	Dry Floor Tool	VP6010000	0	•		•

Kerrick Shockproof Vacuum 90L

Model	Kerrick 2 motor Wet and Dry Vacuum with high impac	Kerrick 2 motor Wet and Dry Vacuum with pump out	Kerrick 3 motor Wet and Dry Vacuum with high impac
Ref. no.	KVAC59PE	KVAC59PE/P	KVAC60PE

Technical specifications

Voltage (V)	240	240	240
Rated power (W)	2 x 1000	2 x 1000	3 x 1000
Air flow rate (L/min)	6000	6000	9000
Vacuum (mbar/kPa)	190/-	190/-	205/-
Sound pressure level at 1.5 m (dB(A) ISO 3744)	65	65	66
Cable length (m)	10	10	10
Container volume (l-max)	90	90	90
Dust bag capacity (L)	56	56	56
Length x width x height (mm)	480 x 620 x 930	480 x 620 x 930	480 x 620 x 930
Net weight (kg)	23	23	26

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

Accessories	Ref. no.	Min. required	Kerrick 2 motor Wet and Dry Vacuum with high impac	Kerrick 2 motor Wet and Dry Vacuum with pump out	Kerrick 3 motor Wet and Dry Vacuum with high impac
Extension Tube					
Chrome Extension 38mm	VP2511600	0	●	●	●
PVC Extension Tube - 500mm	VP2512000	0	○	○	○
Crevice Nozzle					
CREVICE TOOLI D.40	VP2511610	0	●	○	●
Round Brush Nozzle					
ROUND BRUSH	VP2511615	0	●	○	●
Other					
Antifoam Device	VP6200150	0			○
Carpet Tool	VP2512610	0			○
Dry Floor Tool	VP6010000	0	●	○	●
Squeegee, Blade, Skirt and Splash Guard					
Squeegee Tool	VP6010011	0	●	●	●
Filter					
Cartridge Filter	VP2512743	0			○
Nylon Filter	VP3001225	0	○	○	
Textile Filter - SUITS KVAC59PE	VP6730000	0	●	○	●
Vacuum Accessory Set					
50mm Accessory Set	VP5830022	0	○	○	○

Kerrick Shockproof Vacuum 90L

Accessories		Ref. no.	Min. required	Kerrick 2 motor Wet and Dry Vacuum with high impac	Kerrick 2 motor Wet and Dry Vacuum with pump out	Kerrick 3 motor Wet and Dry Vacuum with high impac
Hose Vacuum Cleaner						
	Flexible Hose - 2.5 metre	VP6010648	0	•	•	•
Filter Bag						
	Paper Filter Bag with cap - 19 litre (10 pack)	VP6830030	0	○	○	○