



CREATING A CLEANER, SAFER, HEALTHIER WORLD.

T500 | Walk-Behind Scrubber

Product Specifications

FEATURE	650 mm Disk	700 mm Disk	800 mm Disk	700 mm Cylindrical	700 mm Orbital
Productivity (per hour) Theoretical Max	2,657 m²/hr	2,861 m²/hr	3,270 m²/hr	2,861 m²/hr	2,601 m²/hr
Estimated Coverage* - Conventional	1,911 m²/hr	2,070 m²/hr	2,389 m²/hr	2,070 m²/hr	1,882 m²/hr
Estimated Coverage* - ec-H2O NanoClean®	2,148 m²/hr	2,200 m²/hr	2,538 m²/hr	2,200 m²/hr	2,000 m²/hr
BRUSH DRIVE SYSTEM					
Scrub motor	2x 24 VDC, 0.75 hp / 0.55 Kw	2x 24 VDC, 0.75 hp / 0.55 kW	2x 24 VDC, 0.75 hp / 0.55 kW	2x 24 VDC, 0.63 hp / 0.47 kW	24 VDC, 0.75 hp / 0.55 kW
Brush Pad RPM	220 RPM	220 RPM	220 RPM	1500 RPM	2200 RPM
Brush down pressure	low: 18 kg med: 36 kg high: 54.5 kg	low: 18 kg med: 36 kg high: 54.5 kg	low: 18 kg med: 36 kg high: 54.5 kg	low: 18 kg med: 36 kg high: 54.5 kg	low: 50 kg med: 63.5 kg high: 77 kg
SOLUTION/RECOVERY SYSTEM					
Solution tank capacity	85 L				
Recovery tank capacity	102 L				
Vacuum motor	24 VDC, 0.63 hp / 0.47 kW				
Vacuum water lift	1170 mm				
Vacuum water lift - Quiet-Mode™	810 mm				
CLEANING TECHNOLOGY					
Conventional	Standard				
ec-H2O NanoClean	Optional				
Severe Environment™ (optional only with ec-H2O NanoClean)	Optional				
Severe Environment detergent tank capacity	2.5 L				
BATTERY SYSTEM					
System Voltage	24 Volt				
Battery Types - 4 required Wet 225AH Wet 260AH Sealed AGM 220AH	Standard Optional Optional				
Battery run time - WET 260AH (up-to hours)**	5.9	5.9	5.4	5.4	4.9
On-board or off-board charger	Standard				
Smart-Fill™ Automatic Battery Watering Tank Capacity (Option)	2.5 L				

Product Specifications (continued)

	650 mm Disk	700 mm Disk	800 mm Disk	700 mm Cylindrical	700 mm Orbital
PROPELLING SYSTEM					
Scrubbing speed	4.0 kph				3.7 kph
Transport speed	4.3 kph				
Aisle turnaround width	1499 mm	1514 mm	1565 mm	1514 mm	1499 mm
MACHINE SPECIFICATIONS					
Length	1486 mm	1501 mm	1552 mm	1501 mm	1486 mm
Width	700 mm	750 mm	850 mm	780 mm	710 mm
Height	1100 mm	1100 mm	1100 mm	1100 mm	1100 mm
Squeegee width	973 mm	1049 mm	1234 mm	1234 mm	1049 mm
Weight (without batteries)	145 kg	150 kg	161 kg	168 kg	168 kg
Weight (with batteries)	277 kg	281 kg	293 kg	299 kg	299 kg
GVW	363 kg	367 kg	379 kg	386 Kg	386 Kg
Sound level (operator's ear)***	66.5 dBA	66.5 dBA	66.5 dBA	66.4 dBA	67.0 dBA
Quiet-Mode™ (operator's ear)***	61.7 dBA	61.7 dBA	61.7 dBA	61.8 dBA	60.6 dBA
*Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook. **Up to run-times are based on continuous scrubbing run-times, 260AH batteries, Quiet-Mode setting, low down pressure, ec-H2O off. ***Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment manufacturers & OSHA. Specifications are subject to change without notice.					