



REINVENT HOW THE WORLD CLEANS



# S10

## Industrial-strength walk-behind sweeper

Clean in close quarters and wide-open spaces with the Tennant S10 walk-behind sweeper. This compact, heavy-duty sweeper is engineered to clean even the harshest industrial environments.



**The S10 features two powerful batteries** for fume-free, long-running performance.



**Reduce maintenance costs** with durable, corrosion-proof construction, while the wrap-around bumper protects machine and facility.



**Fully variable forward and reverse functions** ensure easy maneuverability, in any direction, while the ergonomic handle ensures operator comfort.

# Inside the S10

- 1. Large capacity steel hopper** – free-floating hopper holds up to 150 lb / 68 kg, 2.8 ft<sup>3</sup> / 79 L of debris.
- 2. Standard dust filtration** – 49 ft<sup>2</sup> / 4.6 m<sup>2</sup> panel filter captures dust down to 3 microns @ @99.97% efficiency.
- 3. Mechanical filter shaker** – automatically timed, circular hammer design.
- 4. Onboard charger** – plugs into standard 110V outlet. Makes changing easy and accessible.
- 5. Ergonomic handle** – designed for maximum control and comfort; height adjustable with three settings (simple tools required).



## S10 specifications

| FEATURE                                                                      | SPECIFICATION                                          |
|------------------------------------------------------------------------------|--------------------------------------------------------|
| Cleaning path                                                                | 860 mm                                                 |
| Main brush length (tubular)                                                  | 660 mm                                                 |
| Side brush diameter (disk)                                                   | 430 mm                                                 |
| Debris hopper: volume capacity   weight capacity                             | 79 L   68 kg                                           |
| Battery type                                                                 | 24V system, (2) 12V, 155 Ah                            |
| Propelling motor                                                             | 1.0 hp / 0.75 kW                                       |
| Propel speed forward (variable to)                                           | 4.7 km/h                                               |
| Propel speed reverse (variable to)                                           | 4.7 km/h                                               |
| Gradeability: full hopper   empty hopper                                     | 5 deg / 8.75%   7 deg / 12.2%                          |
| Filter area                                                                  | 4.6 m <sup>2</sup>                                     |
| Shaker mechanism                                                             | Automatic timed                                        |
| Vacuum fan: motor   speed   diameter                                         | 0.75 kW   2,000 rpm   230 mm                           |
| Length                                                                       | 1,600 mm                                               |
| Width                                                                        | 925 mm                                                 |
| Height: handle in lowest position   in middle position   in highest position | 940 mm   1,000 mm   1,070 mm                           |
| Weight                                                                       | 272 kg                                                 |
| Minimum aisle turn                                                           | 1,730 mm                                               |
| Sound level (operator's ear)                                                 | 73 dBA                                                 |
| Warranty                                                                     | See your local representative for warranty information |

*Specifications subject to change without notice.*

For a demonstration or additional information, call **1800 226 843** or email **contactus@tennantco.com**

s10-brochure-en-au 11/23

©2023 The Tennant Company logo and other trademarks designated with the symbol "®" are trademarks of Tennant Company registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors. All rights reserved.

**Tennant Australia**  
Unit 2, 10 Johnston Crescent  
Horsley Park NSW 2175  
T: 1800 226 843 (FREE CALL)  
T: +61 2 9839 9700  
[www.tennantco.com.au](http://www.tennantco.com.au)  
[contactus@tennantco.com](mailto:contactus@tennantco.com)

**Tennant New Zealand**  
18 Onslow Ave, Papatoetoe,  
Auckland, 2104  
T: +64 9 253 9013  
F: +64 9 253 9015  
[www.tennantco.co.nz](http://www.tennantco.co.nz)  
[contactus@tennantco.com](mailto:contactus@tennantco.com)