



REINVENT HOW THE WORLD CLEANS



T1581

Ride-on floor scrubber

Productivity boost

Enhance your cleaning performance and keep your floors looking their best with a versatile and user-friendly mid-sized ride-on scrubber. T1581 effectively cleans large hard-floor surfaces with light-to-medium dirt and stains in areas such as logistics, retail and manufacturing.



Large tank capacity

Extend runtime with large 237 L recovery tank capacity and up to 4 hours of operation with fully-charged battery.



Simple operation

User-friendly operator controls featuring one-button cleaning start-up and three pre-set scrubbing programs simplify operation and training.



Versatile cleaning performance

Maintain consistent cleaning results across uneven surfaces with self-leveling brush system that automatically adjusts to the floor surface.

Inside the T1581

1. **Simple operation** with three pre-set programs, allowing operator to select the program that best fits their cleaning need.

2. **Maintain cleaning performance** across uneven surfaces with self-leveling system that automatically adjusts the scrub deck height to a floor's surface.

3. **Quick, mess-free tank draining** with large, pinch-style recovery tank drain hose.
4. **Large-capacity solution tank** to clean effectively with fewer dump/fill cycles.

5. **Consistent water pick-up** with durable v-shaped squeegee design and standard Linatex® squeegee blades.

6. **Reduce maintenance time** by easily accessing daily maintenance and service areas with service-friendly design.



T1581 specifications

FEATURE	SPECIFICATION	
	DISK	CYLINDRICAL
Cleaning path	1,050 mm	1,000 mm
Productivity theoretical max*	6,458 m²/h	7,085 m²/h
Scrubbing speed	7.2 kmh	
Brush speed	200 rpm	1,000 rpm
Brush pressure	116 kg	37 kg
Solution tank capacity	218 L	
Recovery tank capacity	237 L	
Battery run time**	up to 4 hours	
Battery voltage (240Ah Gel Battery)	6x 6V	
Dimensions (LxWxH)	2,006 x 1,376 x 1,508 mm	
Squeegee width	1,380 mm	
Weight (with heaviest battery)	840 kg	865 kg
External radius (wall to wall)	2,440 mm	2,570 mm
Maximum ramp climb	16%	
Sound level (operator's ear)***	76 dBA	79 dBA

Specifications subject to change without notice.
* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.
** Run times are based on Continuous Scrubbing Run Times.
*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

For a demonstration or additional information,
call **1800 226 843** or email **contactus@tennantco.com**

Tennant Australia
Unit 2, 10 Johnston Crescent
Horsley Park NSW 2175
T: 1800 226 843 (FREE CALL)
T: +61 2 9839 9700
www.tennantco.com.au
contactus@tennantco.com

Tennant New Zealand
18 Onslow Ave, Papatoetoe,
Auckland, 2104
T: +64 9 253 9013
F: +64 9 253 9015
www.tennantco.co.nz
contactus@tennantco.com